

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 April 2001 (26.04.2001)

PCT

(10) International Publication Number
WO 01/29514 A1

(51) International Patent Classification⁷: **G01C 21/26**

(21) International Application Number: **PCT/US00/41294**

(22) International Filing Date: 19 October 2000 (19.10.2000)

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
60/160,274 19 October 1999 (19.10.1999) **US**

(71) Applicant: **MAGELLAN DIS, INC.** [US/US]; 2950 Waterview, Rochester Hills, MI 48309 (US).

(72) Inventors: **SPENCER, Larry, E.**; 525 Joslyn Road, Lake Orion, MI 48362 (US). **MOUSER, Mike**; 2451 Clinton Hills Road, Ortonville, MI 48462 (US). **MILLINGTON, Jeffrey, A.**; 3390 Greenwood Drive, Rochester Hills, MI 48309 (US). **STEVENS, Roger, A.**; Plano, TX (US). **HOOK, Christopher** (deceased).

(74) Agent: **CARLSON, John, E.**; Suite 350, 400 West Maple, Birmingham, MI 48009 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **PORTABLE VEHICLE NAVIGATION SYSTEM**



(57) Abstract: A navigation system includes an operator interface module (OIM) including a display and keypad. A computer module (computer module) includes a CPU, map database and the motion and position sensors. A docking station is fixedly mounted in each of a plurality of vehicles. The docking station includes an electrical connector connected to the vehicle power supply and an electrical connector connected to a GPS antenna and an electrical connector connected to a display extension harness. The computer module and OIM are transportable among each of the vehicles. The computer module slides into the docking station and simultaneously makes electrical contact with the vehicle power supply, GPS antenna and display extension harness. The OIM is connected to the display extension harness, thereby connecting the OIM to the computer module. The OIM and computer module are thus transportable among multiple vehicles having the appropriate docking station.



WO 01/29514 A1

PORTABLE VEHICLE NAVIGATION SYSTEM

BACKGROUND OF THE INVENTION

The present invention relates generally to vehicle navigation systems and more particularly to a vehicle navigation system, at least significant components of which are transportable between vehicles. Vehicle navigation systems include many expensive components, including a CPU with mass storage, such as a hard drive, CD or DVD, for storing a map database. Navigation systems further include navigational sensors, such as a GPS receiver, accelerometers, gyros, compass, etc. A navigation system further includes a user interface interacting with the CPU, such as a display, audio speaker, and an input device, such as a keypad or mouse. Installation of the known vehicle navigation systems into the vehicle is difficult and must be performed by an experienced trained technician. Although many households own more than one vehicle, the high cost of many of the vehicle navigation system components make installation of a vehicle navigation system into each of the household vehicles impractical.

SUMMARY OF THE INVENTION

The present invention provides a vehicle navigation system which is easily transportable by a consumer between vehicles. More particularly, at least significant components of the vehicle navigation system are transportable between vehicles. The vehicle navigation system of the present invention includes an operator interface module ("OIM") which includes the user input devices, such as a keypad, and output devices, such as a display and audio speaker. The navigation system further includes a computer module which includes a CPU, mass storage (such as a hard drive), accelerometers and GPS receiver.

In one embodiment of the present invention, the navigation system further includes a docking station with a plurality of electrical connectors. The docking station is fixedly mounted in the vehicle. The computer module is removably mounted in the docking station and is electrically connected via the docking station

to the OIM. The vehicle power supply is electrically connected to the computer module via the docking station. A GPS antenna fixedly mounted to the vehicle is also connected to the computer module via the electrical connector on the docking station.

5 A docking station and GPS antenna are installed in each of at least two vehicles. The vehicle power supply in each vehicle is also connected to the electrical connector of the docking station. The OIM and computer module, which comprise the most expensive components of the vehicle navigation system are transportable between (or among) the vehicles. The computer module is easily slid
10 into a locking position in a docking station, simultaneously making electrical connection with the GPS antenna, vehicle power supply and display extension harness. The OIM is then connected to the docking station. The OIM and computer module can be moved from vehicle to vehicle. Alternatively, a different OIM can be installed in each vehicle, with the computer module being
15 transportable among vehicles.

In this manner, the most expensive components of the vehicle navigation system, contained in the OIM and computer module, need not be purchased for each vehicle. The docking station and GPS antenna, "permanently" installed in each vehicle, are significantly less expensive than the OIM and computer module.

20 In another embodiment of the present invention, the navigation system is completely "portable," i.e. the entire navigation system is movable between vehicles, without any components being installed in either vehicle.

BRIEF DESCRIPTION OF THE DRAWINGS

25 Other advantages of the present invention will be readily appreciated as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings wherein:

Figure 1 is a navigation system of the present invention according to a first embodiment;

30 Figure 2 is a schematic of the computer module of Figure 1;

Figure 3 is an enlarged view of the OIM of Figure 1;

Figure 4 demonstrates the transportability of the navigation system of Figure 1;

Figure 5 is a navigation system of the present invention according to a second embodiment; and

5 Figure 6 demonstrates the portability of the navigation system of Figure 5.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

The present invention provides a vehicle navigation system 20 generally comprising an Operator Interface Module ("OIM") 22, a docking station 24 and a
10 computer module 26. The OIM 22 includes output devices, such as a display 28 and an audio speaker 30 (directed toward the rear of the display 28). The OIM further includes user input devices, such as buttons and a directional keypad, collectively referenced as numeral 32 in Figure 1. The OIM 22 may alternatively include additional or alternate input devices, such as a keyboard, mouse,
15 microphone, track pad, etc. The OIM 22 is connected electrically with a display harness 34 which is removably electrically connected to a display extension harness 36, which in turn is removably electrically connected to an electrical connector 38 on the docking station 24.

The computer module 26 includes an electrical connector 40
20 complementary to the electrical connector 38 on the docking station 24. The computer module 26 is removably secured in the docking station 24 and selectively mechanically locked in the docking station 24 via latches 42. When computer module 26 is slid into docking station 24, the connector 40 on the computer module 26 is automatically aligned and mated with the electrical connector 38 on
25 the docking station 24 and the mechanical latches 42 mechanically retain the computer module 26 in the docking station 24.

A vehicle wire harness 44 is wired to the vehicle electrical power supply (shown schematically at 46) and removably secured to the electrical connector 38. A GPS antenna 48 is connected via an antenna harness 50 which is removably
30 secured to the electrical connector 38 in docking station 24. The GPS antenna 48

includes means for mounting the GPS antenna 48 to the outer surface of a vehicle, such as a magnet, suction cup, clips or fasteners (not shown). When the computer module 26 is docked in the docking station 24, the electrical connectors 38, 40 are mated, thus providing an electrical connection of the computer module 26 to the harnesses 36, 44 and 50 and their corresponding elements, namely the OIM 22, vehicle power supply 46 and GPS antenna 48, respectively. The computer module is selectively, manually removable by a user by unlatching the latches 42 and sliding the computer module 26 out of the docking station 24, at which time the electrical connectors 38, 40 are disconnected.

10 The computer module 26 is shown schematically in Figure 2. The computer module 26 generally includes a CPU 56. The computer module 26 further includes a mass storage 58, such as a hard drive including a database 60 of roads to be traveled by the vehicle navigation system 20 (Figure 1). Alternatively, the mass storage could comprise a CD ROM, DVD, RAM, magnetic memory, optically readable media or integrated circuit, etc.

15 The CPU 26 stores data 61a, 61b, 61c relating to each of a plurality of vehicles, preferably in mass storage 58. For example, the data 61a-c for each vehicle includes information based upon which the CPU 56 propagates the position of the navigation system 26 relative to the earth or relative to the database 60. For example, the data 61 could include information indicating the orientation of the computer module 26 (and thus the multi-axis accelerometer 64) in the associated vehicle. The CPU 56 propagates the position based upon data from the accelerometer 64 and based upon data 61a-c indicating the orientation of the accelerometer 64 within the associated vehicle.

25 The orientation information can be user defined or learned when the computer module 26 is first installed into the associated vehicle. For example, when there is very little noise in the signal from the accelerometer 64 and it is determined that the vehicle is not moving, it is easy for the CPU 56 to determine the direction of gravity relative to the orientation of the accelerometer 64 in the vehicle. When the vehicle then accelerates, most of the acceleration is initially in

the forward direction, which is then learned by the CPU 56 monitoring the data from the accelerometer 64. The lateral direction is defined as perpendicular to gravity and the forward direction. This technique is described in more detail in co-pending application Serial Number 09/159,164 filed September 23, 1998 and
5 entitled "Calibration of Orientation of Multi-Axis Accelerometer," which is hereby incorporated by reference.

The computer module 26 also houses a GPS receiver 62 and a multiple axis accelerometer 64, together providing position and motion data to the CPU 56. Other known sensors for use in vehicle navigation systems could also be housed
10 within the computer module 26, such as gyros 65, a compass 66, an altimeter 67, etc. The CPU 56 and GPS receiver 62 are electrically connected (connections not shown) to the electrical connector 40 for connection in turn to the OIM 22, vehicle power supply 46 and GPS antenna 48 (Figure 1).

The OIM 22 is shown in more detail in Figure 3. In Figure 3, the OIM 22
15 is shown displaying a "select vehicle" screen 68 on display 28. The select vehicle screen 68 displays a plurality of vehicle icons 70a, 70b and 70c, each associated with a real vehicle, including vehicles 72, 74. Alternatively, icons can be associated with particular users, who are each in turn associated with a vehicle. As can be seen more clearly in Figure 3, the OIM 22 includes a plurality of input
20 devices 32a-i, including a directional keypad or mouse 32i. Through known software techniques, the directional keypad 32i is utilized to highlight a selected one of the plurality of vehicle icons 70a-c (vehicle icon 70a shown selected). After selecting one of the vehicle icons 70a-c, the user selects the selected icon utilizing an "enter" key 32f.

25 Referring to Figure 4, the vehicle navigation system 20 is conveniently transportable between two or more vehicles 72, 74 (two vehicles shown). As illustrated in Figure 4, significant components of the navigation system 20 are transportable between vehicles 72, 74, while the remaining components of the vehicle navigation system 20 are duplicated and installed in each vehicle 72, 74.
30 In the example configuration shown in Figure 4, the computer module 26 and OIM

22 (with display extension harness 34) are transportable between the two vehicles 72, 74. A docking station 24, GPS antenna 48 and the harnesses 36, 44 and 50 are duplicated and installed on each vehicle 72 and 74. A mount 78 for mounting the OIM 22 is also installed in each vehicle 72, 74. Mount 78 is preferably a hook
5 and snap fit retainer, similar to cell phone mounts in vehicles.

To "install" the OIM 22 and computer module 26 into the first vehicle 72, the computer module 26 is slid into a docking station 24 of the first vehicle 72, where it is automatically mechanically docked into the docking station 24 and automatically electrically connected to the vehicle power supply 46, display
10 harness 36 and GPS antenna 48. The OIM 22 is then connected to the display harness 36 by connecting the display harness 34 to display extension harness 36. The OIM 22 is then mounted on mount 78 in the first vehicle 72. When the navigation system 20 is then turned on, the user, utilizing the OIM 22 and the select vehicle screen 68 shown in Figure 3 indicates to the computer module 26
15 which of the two vehicles 72, 74 the computer module 26 and OIM 22 are installed by selecting the icon 70a associated with the first vehicle 72. Based upon the icon 70a selected, the CPU 56 (Figure 2) then selects the data 61a associated with the first vehicle 72 and propagates the position of the vehicle 72 relative to the earth or relative to the database 60 based upon the information from the accelerometer 64
20 together with the data 61a and in combination with information from the GPS 62.

The computer module 26 may be selectively removed from the docking station 24 of the first vehicle 72 and easily installed into the docking station 24 of the second vehicle 74. Similarly, the OIM 22 may be removed from the first vehicle 72, connected to the display extension harness 36 in the second vehicle 74
25 and mounted on mount 78 in the second vehicle 74. Alternatively, the OIM 22 may be duplicated and installed in each vehicle 72, 74. After the computer module 26 is installed into the second vehicle 74, the user, using the select vehicle screen 68 of Figure 3 selects the icon 70b associated with the second vehicle 74. Alternatively, the CPU 56 may be able to quickly determine the vehicle into which
30 it has been installed based upon its orientation and based upon its relative

orientation relative to gravity. The CPU 56 (Figure 2) then selects the data 61b associated with the second vehicle 74 and propagates the position of the vehicle 74 relative to the earth or relative to the database 60 based upon the information from the accelerometer 64 together with the data 61b and in combination with
5 information from the GPS 62.

As in known navigation systems, the current location of the vehicle 72, 74 is displayed on the display 28 of OIM 22 relative to the surrounding roads. Many techniques for the integration of information from the various position-determining devices are known. Map-matching is also a well-developed technique for use in
10 navigation systems. Any of these techniques for determining the position of the vehicle 72, 74 relative to the database 60 of roads can be used, as these techniques form no part of the present invention.

As is known in navigation systems, the user can select a destination relative to the database 60 of roads utilizing the input devices 32 and the display 28. The
15 navigation system 20 then calculates and displays a recommended route directing the driver of the vehicle 72, 74 to the desired destination. Preferably, the navigation system 20 displays turn-by-turn instructions on display 28 along with corresponding audible turn-by-turn instructions via an audio speaker (not shown), guiding the driver to the desired destination.

Utilizing the navigation system 20 of the present invention, significant or
20 expensive components of a vehicle navigation system are easily transportable between at least two vehicles 72, 74. Lower cost components of the vehicle navigation system 20 are duplicated and more permanently installed in each vehicle 72, 74. Thus, a household with at least two vehicles 72, 74 is easily able to
25 transport (and thus avoid duplicating) significant components (such as the computer module 26 and/or OIM 22) between vehicles 72, 74.

A completely portable embodiment of the navigation system 80 according to the present invention is shown in Figure 5. In other words, no components are permanently installed in either vehicle and all of the components are easily moved
30 from one vehicle to the other. Except as noted otherwise below, the navigation

system 80 is identical to the embodiment of Figures 1-4 and identical components are given identical reference numerals.

Although the computer module 26 is shown removably mounted in the docking station 24, the separate docking station 24 is not necessary in this embodiment. A single, integral housing could be used for the computer module 26 and for supporting the electrical connectors. In this embodiment, the power is provided via a plug 82, such as a cigarette lighter adapter and a power pack 84, preferably including a battery pack 86. Preferably, the GPS antenna 48 includes a magnet mount, so that it can easily be repeatedly secured and removed from an outer surface of a vehicle. Preferably, the navigation system 80 is provided in a carrying case 90, which holds all of the components of the navigation system 80 during transport.

Referring to Figure 6, the navigation system 80 is easily portable between or among a plurality of vehicles 72, 74. Figure 6 shows the navigation system 80 used in two different vehicles 72, 74. In vehicle 72, the navigation system 80 components reference numerals have been appended with the letter "a"; in vehicle 74, "b."

Use of the navigation system 80 in vehicle 72 is simple. The user first removes all of the components from the case 90. The user then places the GPS antenna 48 on the roof of the vehicle 72 and routes the antenna wire through the door of the vehicle 72. The display 22 is connected to the computer module 26/docking station 24. The computer module 26/docking station 24 can be placed on the floor of the vehicle 73, preferably on the passenger side. The computer module 26/docking station 24 can but need not be secured to the carpet with Velcro. The display 22 is removably mounted, preferably to one of the vehicle's AC vents. A small bracket or hook on the back of the display 22 achieves this purpose. The plug 82 is then connected to a cigarette lighter socket 92 in the vehicle 72. Since the computer module 26/docking station 24 will be in an unknown orientation, the navigation system 80 is then calibrated in the manner described above with respect to the navigation system 20 of Figure 1. During use,

which is the same as for the navigation system 20 of Figure 1, the battery pack 86 provides power backup to the navigation system 80 and can power the navigation system 80 temporarily.

5 In accordance with the provisions of the patent statutes and jurisprudence, exemplary configurations described above are considered to represent a preferred embodiment of the invention. However, it should be noted that the invention can be practiced otherwise than as specifically illustrated and described without departing from its spirit or scope.

CLAIMS

1. A vehicle navigation system comprising:
a computer module including a processor and a map database:
5 a docking station, said computer module selectively matable with
said docking station.
2. The navigation system of Claim 1, wherein the computer module
further includes at least one navigational sensor.
- 10 3. The navigation system of Claim 2, wherein said computer module
further includes a GPS receiver.
4. The navigation system of Claim 2, wherein the computer module
15 further includes at least one accelerometer.
5. The navigation system of Claim 1, wherein said computer module
includes a first electrical connector and said docking station includes a second
electrical connector, said first electrical connector becoming electrically connected
20 to the second electrical connector when the computer module is mated with the
docking station.
6. The navigation system of Claim 5, wherein said first electrical
connector is electrically connected to said CPU.
- 25 7. The navigation system of Claim 6, wherein said first electrical
connector is electrically connected to a GPS receiver on said computer module.
8. The navigation system of Claim 5, further including an operator
30 interface module electrically connected to said second connector.

9. The navigation system of Claim 8, wherein said operator interface module includes a display.

10. The navigation system of Claim 5, wherein said docking station is
5 fixedly mounted in a first vehicle.

11. The navigation system of Claim 1, wherein said computer module further includes means for determining a position of the navigation system relative to the map database.
10

12. The navigation system of Claim 11, further including means for determining a route from a beginning point to an ending point via said map database.

13. The navigation system of Claim 12 wherein the computer module includes an inertial sensor generating a motion signal, said processor propagating position based upon said motion signal.
15

14. A vehicle navigation system comprising:

a docking station fixedly mounted in a first vehicle;

a computer module including a CPU, map database, GPS receiver and at least one accelerometer, the computer module comprising a self-contained unit which is selectively matable with and removable from the docking station, the computer module including a first electrical connector which is electrically connected with a second electrical connector on the docking station when the computer module is mated to the docking station, said second electrical connector being electrically connected to a power supply in the first vehicle; and

an operator interface module selectively electrically connectable to the CPU of the computer module, said operator interface module including a display and a plurality of user activatable switches.

15. The vehicle navigation system of Claim 14, wherein the computer module further includes means for determining a position of the vehicle navigation system relative to the map database and means for determining a route via the map database from the current location to a destination in the map database selected by the operator interface module.

16. The navigation system of Claim 15 further including a second docking station fixedly mounted in a second vehicle, said computer module selectively matable with said second docking station.

17. The navigation system of Claim 16 wherein said operator interface module is selectively connectable to said first docking station or said second docking station.

18. A vehicle navigation system comprising:

a computer module including a CPU, map database, first vehicle data, second vehicle data, and at least one of an inertial sensor or a GPS receiver;

5 said computer module utilizing said first vehicle data when the computer module is installed in the first vehicle and said second vehicle data when said computer module is installed in the second vehicle.

19. The vehicle navigation system of Claim 18 further including a user
10 interface for providing user input regarding whether to use the first vehicle data or the second vehicle data.

20. The navigation system of Claim 19, wherein the user interface
15 includes a display and user operable switches for selecting between the first vehicle data and second vehicle data.

21. The vehicle navigation system of Claim 18, wherein the first vehicle
data includes information regarding the orientation of the computer module relative
to the first vehicle when the computer module is installed in the first vehicle and
20 the second vehicle data includes information regarding the orientation of the
computer module relative to the second vehicle when the computer module is
installed in the second vehicle.

22. The navigation system of Claim 21, wherein the CPU propagates
25 position of the vehicle navigation system based upon the first vehicle data when the
computer module is installed in the first vehicle and based upon the second vehicle
data when the computer module is installed in the second vehicle.

23. A method for using a vehicle navigation system including the steps of:

- a. removably securing a CPU and inertial sensor in a first vehicle;
- 5 b. removing the CPU and at least one inertial sensor from the first vehicle;
- c. after step b., removably securing the CPU and the at least one inertial sensor in a second vehicle.

10 24. The method of Claim 23 further including the steps of propagating the position of the first vehicle after said step a. based upon data from the at least one inertial sensor.

15 25. The method of Claim 24, further including the step of propagating the position of the second vehicle based upon data from the inertial sensor after said step c.

26. The method of Claim 25, further including the steps of:
storing first vehicle data regarding the orientation of the at least one
20 inertial sensor when installed in the first vehicle; and
storing second vehicle data regarding the orientation of the at least one inertial sensor when installed in the second vehicle.

27. The method of Claim 26 further including the steps of
25 propagating the position of the first vehicle based upon the first vehicle data when the CPU and first inertial sensor are installed in the first vehicle; and
propagating the position of the second vehicle based upon the second vehicle data when the CPU and at least one inertial sensor are
30 installed in the second vehicle.

28. The method of Claim 27 further including the step of manually selecting whether to use the first vehicle data or second vehicle data via a user input device.

5 29. The method of Claim 28, wherein step a. includes the step of mating said CPU and at least one inertial sensor with a docking station mounted in the first vehicle.

30. A method for installing a vehicle navigation system including the
10 steps of:

- a. electrically connecting a first docking station to a vehicle power supply of a first vehicle;
- b. mounting the first docking station in the first vehicle; and
- c. removably mating a CPU and map database to the first
15 docking station.

31. The method of Claim 30 further including the step of removably securing a gps receiver in the first vehicle during said step c

20 32. The method of Claim 30 further including the step of removably securing an accelerometer in the first vehicle during said step c.

33. The method of Claim 30 further including the step of removably connecting a display to the first docking station.
25

34. The method of Claim 30 further including the steps of:
d. removing the CPU and map database from the first docking station; and
e. after said step d, removably mating said CPU and said map
30 database to a second docking station mounted in a second vehicle.

35. A method for installing a vehicle navigation system including the steps of:

- a. electrically connecting a first docking station to a vehicle power supply of a first vehicle;
- 5 b. mounting the first docking station in the first vehicle; and
- c. removably mating a CPU and an inertial sensor to the first docking station.

36. The method of Claim 35 wherein said inertial sensor is an
10 accelerometer.

37. The method of Claim 36 further including the step of removably connecting a display to the first docking station.

15 38. The method of Claim 35 further including the steps of:

- d. removing the CPU and map database from the first docking station; and
- e. after said step d, removably mating said CPU and said map database to a second docking station mounted in a second vehicle.

20

39. A method for using the vehicle navigation system including the steps of:

- a) storing first vehicle data regarding operation of the vehicle navigation system when installed in a first vehicle;
- 25 b) storing second vehicle data regarding operation of the vehicle navigation system when installed in a second vehicle;
- c) selectively retrieving either the first vehicle data or the second vehicle data; and
- d) propagating the position of the vehicle navigation system based
30 upon the first vehicle data or second vehicle data selected in said step c).




Fig-1






Fig-2

Fig-3

Fig-4





Fig-5

Fig- 6

INTERNATIONAL SEARCH REPORT

Int. National Application No

PCT/US 00/41294

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G01C21/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 816 804 A (MAGNETI MARELLI SPA) 7 January 1998 (1998-01-07) the whole document	1,5,6, 9-12
A	US 5 760 742 A (JANKY JAMES M ET AL) 2 June 1998 (1998-06-02) claim 1	1-13
A	US 4 733 356 A (GAUS HERMANN ET AL) 22 March 1988 (1988-03-22) abstract	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

27 March 2001

Date of mailing of the international search report

03/04/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

De Buyzer, H

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. J. Appl. Application No

PCT/US 00/41294

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 0816804	A	07-01-1998	IT	T0960548 A	29-12-1997
US 5760742	A	02-06-1998	NONE		
US 4733356	A	22-03-1988	DE	3445668 C	02-01-1986
			GB	2168485 A, B	18-06-1986
			JP	1687857 C	11-08-1992
			JP	3052062 B	08-08-1991
			JP	61149983 A	08-07-1986